Han® 3 HPR

Surface mounted housing
with top entry, long construction

Features

- Long construction, therefore large cabling space
- Also suitable for Han-Quintax® inserts
- M25 cable entry
- Suitable for extreme environmental conditions
- Highly EMC resistant
- For interfaces, that have to be protected and shielded

Technical characteristics

Material		Zinc die-cast
Surface:	powder-coated	RAL 9005 (black) RoHS conforming
	black chromate	not RoHS conforming
Tightening torque for Fixing screws (M4)		min. 1 Nm
Limiting temperatures		-40 °C ... 125 °C
Degree of protection acc. to EN 60 529 in locked position		IP 68

Identification	Part-Number	M	Drawing	Dimensions in mm
Surface mounted housing with top entry long construction				
With closed bottom and feed through hole for fixing screws				
black chromate	19 40 003 0951	25		
powder-coated	19 40 703 0951	25		
With closed bottom and tapped blind hole for fixing screws				
black chromate	19 40 003 0953	25		
powder-coated	19 40 703 0953	25		

HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | D-32339 Espelkamp
Fon: +49 57 72 47-97100 | Fax: +49 57 72 47-124
Internet: www.HARTING.com | E-Mail: HARTING.Electric@HARTING.com